

Suitable pitch
Current Rating

0.5mm
1A

Material and Plating

Barrel PB / Ni + Au
Spring SWP / Ni + Au
Receptacle PB / Ni + Au

プローブラインナップ

| Spring force | Stroke used | Full St |
|--------------|-------------|---------|
| Initial | 1mm | 1.5mm |
| 13g | 31g | 40g |

SB-1

Material :BeCu
Plating :Au

SB-2

Material :BeCu
Plating :Au

SB-3

Material :BeCu
Plating :Au

SB-5

Material :SK
Plating :Au

| Spring force | Stroke used | Full St |
|--------------|-------------|---------|
| Initial | 0.7mm | 1mm |
| 22g | 34g | 40g |

SB-10

Material :BeCu
Plating :Au

SB-20

Material :BeCu
Plating :Au

SB-30

Material :BeCu
Plating :Au

SB-50

Material :SK
Plating :Au

| Spring force | Stroke used | Full St |
|--------------|-------------|---------|
| Initial | 1.3mm | 2mm |
| 11g | 25g | 32g |

SB-200LT

Material :SK
Plating :Au

SB-500LT

Material :SK
Plating :Au

ソケットラインナップ

Wire crimping type
SBR-(ex.ST) HR 100mm/300mm
(Lead wire length 100mm/300mm)

Reference hole diameter : φ0.42