

## Probe specifications

Suitable pitch: 0.8mm  
Current rating: 2.5A

## Material and Plating

Plunger Check below  
Barrel PB / Ni+Au  
Spring SWP / Ni+Au  
Receptacle PB / Ni+Au

## Probe & Socket line-up

Spring force	St used	Full St
Initial	1.3mm	2mm
15g	45g	60g

**SF-1V**

Material: BeCu  
Plating: Au

**SF-2V**

Material: BeCu  
Plating: Au

**SF-3V**

Material: BeCu  
Plating: Au

**SF-5V**

Material: BeCu  
Plating: Au

**SF-5TV**

Material: SK  
Plating: Au

---

Spring force	St used	Full St
Initial	0.7mm	1mm
30g	50g	60g

**SF-10V**

Material: BeCu  
Plating: Au

**SF-20V**

Material: BeCu  
Plating: Au

**SF-30V**

Material: BeCu  
Plating: Au

**SF-50V**

Material: BeCu  
Plating: Au

**SF-50TV**

Material: SK  
Plating: Au

**SFR-STV**

**SFR-FV**

Reference hole diameter:  $\phi 0.67$

※ Wire crimping type  
SFR- 型号 HR100/HR300  
[Lead wire 100mm / 300mm]

Spring force	St used	Full St
Initial	1.3mm	2mm
15g	40g	50g

**SF-200SV**

Material: SK  
Plating: Au

**SF-200V**

Material: SK  
Plating: Au

**SF-500SV**

Material: SK  
Plating: Au

**SF-500V**

Material: SK  
Plating: Au

**SFR-100FV**

Reference hole diameter:  $\phi 0.67$

※ Wire crimping type  
SFR-100FV HR100/HR300  
[Lead wire 100mm / 300mm]