

Suitable pitch 0.65mm
Current Rating 1.5A

Material and Plating

Barrel PB / Ni + Au
Spring SWP / Ni + Au
Receptacle PB / Ni + Au

プローブラインナップ

Spring force	Stroke used	Full St
Initial 20g	1.3mm 45g	2mm 60g

SJ-1

Material :BeCu
Plating :Au

SJ-2

Material :BeCu
Plating :Au

SJ-3

Material :BeCu
Plating :Au

SJ-5

Material :BeCu
Plating :Au

SJ-5Y

Material :SK
Plating :Au

Spring force	Stroke used	Full St
Initial 30g	1.5mm 50g	1.5mm 60g

SJ-10

Material :BeCu
Plating :Au

SJ-20

Material :BeCu
Plating :Au

SJ-30

Material :BeCu
Plating :Au

SJ-50

Material :BeCu
Plating :Au

Spring force	Stroke used	Full St
Initial 20g	1.3mm 45g	2mm 60g

SJ-200

Material :SK
Plating :Au

SJ-500

Material :SK
Plating :Au

ソケットラインナップ

Reference hole diameter $\phi 0.53$
丸ポスト
材質:BS (Au仕上)

Reference hole diameter $\phi 0.53$

Reference hole diameter $\phi 0.54$

Reference hole diameter $\phi 0.55$

SJR-STL/FT/FR Wire crimping type SJR-(ex.STL) HR 100mm/300mm (Lead wire length 100mm/300mm)